

**250mW Up to 12 RF Channels Wireless Video / Audio Transmission**

Radiocontact Ltd. manufacture a wide range of wireless transmission equipment for the export, market within 1.3GHz - 1.4GHz allowing for up to 12 separate factory set channels with output power levels between 250mW - 500mW

A field trial is necessary on all sites to ensure local conditions are favourable.

**Licensing authority approval may be required to operate this equipment**

**Transmitter Specification**

**CCT25/XL**

- Output power 250mW
- Frequencies 1.2MHz - 1.4MHz
- Channels 12 factory set
- Video Input 1V p-p via BNC
- Audio input Line In (optional)
- Supply voltage 12VDC @ 0.5A
- Size (mm) 150x65x30
- Weight (gr) 300



**CTR90S**

**Receiver Specification**

Export Range Wireless Video/Audio Receiver  
 suitable for: CCT25/XL

- Input Sensitivity -90dBm
- Frequency Range 1-1.4GHz
- I.F. 480MHz
- Bandwidth 20MHz Nominal
- Image Rejection 40dB
- Demodulation PLL
- De-emphasis CCIR PAL 401-1
- Video Output 1V, into 75R
- Audio Output Line out
- Voltage 12VDC @ 0.5A

**VIDEO  
&  
AUDIO**