

CCT2440 - VIDLINK

Wireless Video Transmission Recommended Range:

- < 500m standard
- < 1Km with CCT2440/YAG10

10mW - 4 RF Channels UK/FU Wireless Video & Audio Transmission

Small and compact design with omni directional antennas.

4 user selectable radio channels (Up to 4 pairs may operate in the same site).

RF input filter - Omni directional antennas - Supplied with mounting brackets.

High gain antennas available

A field trial is necessary on all sites to ensure local conditions are favourable.



Main Features

- Range: 500m standard version,
- 1Km long range version, with CCT2440/YAG10.
- 4 RF Channels
- Line In / Line Out Audio
- Lightweight Design
- Supplied with Mounting Bracket
- Weather proof boxes to IP65 available
- Compliant with ETSI EN 300-440-1



Long Range Receiver Antenna CCT2440/YAG10 Dimensions: 610x115x60mm Weight: 1.15Kg approx.



Transmitter Specification

Output power 10mW Supply voltage 12VDC Current 130mA

Frequencies 2.410GHz. 2.430GHz. 2,450GHz, 2,470GHz,

1V p-p via BNC

Video Input Audio input Line In Size (mm) 170x65x30 Weight (gr) 300

Receiver Specification

Input Sensitivity -90dBm Supply Voltage 12VDC. Current 300mA. Frequency Range 2.4 - 2.8GHz Video Output 1V p-p. Audio Output Line Out 170x65x30 Size (mm)

Weight (gr) 300